

TECHNICAL DATA

High performance Water activated Kraft paper Tape
Grade No. TL-K1309

► Product Description

TL-K1309 is a **high performance** tape based on Kraft paper with water activated adhesive and designed for bottom splicing **release paper** for making Synthetic Leather.

The tape has features such as excellent heat resistance, high tensile & tear strength

► Product Data

Properties	Unit	Value
Base Weight	GSM	120 +/- 7
Total Thickness	U	158 +/- 15
Tear Strength	nN/15mm HD	2150 +/- 550
Tensile Strength	nN/15mm HD	145 +/- 30
Temperature Resistance	-	180°C x 10min
Color	-	Khaki
Length	Metres	180
Width	mm	75

► Notes

- When applying Water activated Adhesive tape to any surface, please make sure that the surface should be free from oil or any other surface contaminants such as powder, dust or release agent.
- Adhesive performance should be carefully checked when used on substrates containing plasticizers.
- Water should be evenly applied to the adhesive side of the paper (preferably use applicator)
- Apply the tape with mild pressure and use hot iron to remove the moisture
- The property warranty period is 6 months from the date of shipment when stored under a cool and dry conditions of 25°C±5°C and 40%±20% R.H. in the original packaging. Keep away from water
- The above data are typical properties and should not be taken as a specification.